

Berker Integro Box

Compact installation dimensions combined with various fastening options offer the user a diverse range of easy options to integrate the Berker Integro Box. Various combination options of frame versions from the Design Flow range, in combination with the complete portfolio of Berker Integro – module inserts, offer a wide range of customised installation options.



07

Page

Integro Box with SCHUKO socket outlet	136
Installation sets	136

Product examples

Berker Integro

Box

Dimensions

For dimensions and further technical data please refer to Page 218



Berker Integro Box with Schuko socket outlet and frame, polar white glossy



Berker Integro Box with Schuko socket outlet, hinged cover and on/off switch, polar white glossy



Integro Box/empty housing

Plastic, glossy
polar white similar to RAL 9010

Plastic, lacquered
Chrome matt similar to RAL 9006



Berker Integro Box with Schuko
socket outlet and frame,
chrome matt, lacquered



Berker Integro Box with Schuko
socket outlet, hinged cover and
on/off switch, chrome matt,
lacquered

Integro Box with SCHUKO socket outlet



Integro Box with SCHUKO socket outlet

▶ 216

Rated voltage	250 V~	- with SCHUKO socket outlet, pre-assembled with contact protection box
Rated current	16 A	- confectioned, with 3-core cable with conductor sleeves
Lead	3 x 1.5 mm ²	- rear wall in polar white
Line length	≈ 1 m	

Frames/frames with hinged cover exclusively from Berker Integro, design Flow have to be ordered separately to complete the article.

Suitable for	Order no.	Page
Frame 1gang	9 1827 25 ..	74
Frame with hinged cover	9 1828 25 ..	76

Design	Order no.	PU
polar white glossy	1979 01 09	1
chrome matt, lacquered, socket, black, glossy	1979 01 58	1



Integro Box with SCHUKO socket outlet

▶ 216

- on/off switch		- rear wall in polar white
		- with SCHUKO socket outlet, pre-assembled with contact protection box
		- with rocker switch for switching on/off a lamp
		- with insulating plug
		- pre-assembled, with 3-core lead and 2-core light fitting wire, each with conductor sleeves
Rated voltage	250 V~	
Rated current socket outlet	16 A	
Rated current switch	2 A	
Lead	3 x 1.5 mm ²	
Light fitting cable	2 x 0.75 mm ²	
Line length	≈ 1 m	

Frames/frames with hinged cover exclusively from Berker Integro, design Flow have to be ordered separately to complete the article.

Suitable for	Order no.	Page
Frame 1gang	9 1827 25 ..	74
Frame with hinged cover	9 1828 25 ..	76

Design	Order no.	PU
polar white glossy	1979 11 09	1
chrome matt, lacquered, Socket outlet and switch black glossy	1979 11 58	1

Installation sets



Integro Box mounting set

▶ 216

Frames/frames with hinged cover exclusively from Berker Integro, design Flow have to be ordered separately to complete the article.

- rear wall in polar white
- with contact protection box with double strain relief
- with fixing screws for socket outlet insert

Suitable for	Order no.	Page
SCHUKO socket outlets		from p. 22
Outlets without protective contact		from p. 38
Socket outlets with earthing pin		from p. 41
Socket outlets without earthing contact		from p. 44
Frame 1gang	9 1827 25 ..	74
Frame with hinged cover	9 1828 25 ..	76

Design	Order no.	PU
polar white glossy	1979 00 09	1
chrome matt, lacquered	1979 00 58	1



Integro Box mounting set

▶ 216

- on/off switch



Rated voltage 250 V~
 Rated current switch 2 A
 Conductor cross-section (flexible), with wire end sleeve 0.5 ... 0.75 mm²

- with rocker switch for switching on/off a lamp
- rear wall in polar white
- with contact protection box with double strain relief
- with fixing screws for socket outlet insert
- with insulating plug

Caution!
 Contact protection is only guaranteed if the wire stripping length is 10 mm.

Suitable for	Order no.	Page
SCHUKO socket outlets		from p. 22
Outlets without protective contact		from p. 38
Socket outlets with earthing pin		from p. 41
Socket outlets without earthing contact		from p. 44
Frame 1gang	9 1827 25 ..	74
Frame with hinged cover	9 1828 25 ..	76

Frames/frames with hinged cover exclusively from Berker Integro, design Flow have to be ordered separately to complete the article.

Design	Order no.	PU
polar white glossy	1979 10 09	1
chrome matt, lacquered, Switch black glossy	1979 10 58	1